



# HPE OfficeConnect 1620 Switch Series



## Key features

- Entry-level, smart-managed Layer 2 switches
- 8-, 24-, and 48-port gigabit models are rack-mount capable with included hardware
- 8- and 24-port models run quiet (fanless)
- All models include internal power supplies
- Limited Lifetime Warranty

## Product overview

HPE OfficeConnect 1620 Switch Series are entry configurable switches for small business networking, a step up from unmanaged devices, with features to enhance network security, performance and reliability. The series is part of the OfficeConnect portfolio of Hewlett Packard Enterprise small business networking products.

These Gigabit switches are plug-and-play out of the box, yet network operations can be fine-tuned through features available from a simple Web browser-based GUI, if necessary. Enhance security using virtual LANs, link aggregation, or IGMP Snooping boost uplink performance, and loop prevention enhances network reliability.

The series consists of 8-, 24-, and 48-port 10/100/1000BASE-T models each providing non-blocking gigabit per port performance. All models can be rack mounted and include the necessary rack-mounting hardware; the 8-port model can also be wall mounted. All models come with internal power supplies and localized power cord removing the need to manage external power adapters. The 8- and 24-port models are fanless for silent operation.

HPE OfficeConnect 1620 Switch Series is covered by a Limited Lifetime Warranty.

## Features and benefits

### Management

- Simple Web management

Allows for easy management of the switch even by nontechnical users through an intuitive Web GUI; supports HTTP and HTTP Secure (HTTPS)
- Secure Web GUI

Provides a secure, easy-to-use graphical interface for configuring the switch via HTTPS
- SNMPv1, v2c, and v3

Facilitates management of the switch, as the device can be discovered and monitored from an SNMP management station
- Port mirroring

Enables traffic on a port to be simultaneously sent to a network analyzer for monitoring
- Default DHCP Client mode

Allows the switch to be directly connected to a network, enabling plug-and-play operation; in absence of a DHCP server on the network, the switch will fall back to a unique static address determined by the switch's MAC address
- Network Time Protocol (NTP)

Synchronizes timekeeping among distributed time servers and clients; keeps timekeeping consistent among all clock-dependent devices within the network so that the devices can provide diverse applications based on the consistent time
- Manual network time configuration

Manually set the date and time on the switch in the absence of a NTP server
- Dual flash images

Provide independent primary and secondary operating system files for backup while upgrading

### Quality of service (QoS)

- IEEE 802.1p prioritization with DSCP

Delivers data from the switch to devices based on the priority and type of traffic using Differentiated Services Code Point (DSCP)
- Broadcast control

Allows limitation of broadcast traffic rate to cut down on unwanted network broadcast traffic
- Rate limiting

Sets per-port ingress enforced maximums and per-port, per-queue minimums

**Connectivity**

- Auto-MDI/MDIX

Automatically adjusts for straight-through or crossover cables on all ports

- IEEE 802.3X Flow Control

Provides a flow throttling mechanism propagated through the network to prevent packet loss at a congested node

- Loopback detection

If the switch detects a loop, it disables the source port from forwarding data packets originating from the switch to avoid broadcast storms

- Energy Efficient Ethernet

Compliant with IEEE 802.3az standard requirements to save energy during periods of low data activity

- Port power save mode

Enables a port to operate at the lowest transmission speed or go down during a specific time range on certain days of a week. The port resumes when the effective time period ends

- Cable test

Performs a check on the status of the cable connected to an Ethernet port on the device. The test determines whether a short circuit or open circuit is present on the cable and the approximate length to the fault in the cable

**Performance**

- Half- and full-duplex auto-negotiating capability on every port doubles the throughput of every port

- IGMP Snooping, v1, v2, and v3

Improves network performance through multicast filtering, instead of flooding traffic to all ports

**Layer 2 switching**

- VLAN support and tagging

Supports IEEE 802.1Q with 4,096 simultaneous VLAN IDs

- Jumbo frame support

Supports up to 10 kilobyte frame size to improve the performance of large data transfers

**Resiliency and high availability**

- Link aggregation

Groups together multiple ports (up to a maximum of eight ports per trunk) automatically using Link Aggregation Control Protocol (LACP), or manually, to form an ultra-high-bandwidth connection to the network backbone; helps prevent traffic bottlenecks. Note: 8 port model support 4 trunks, 24 port model support 8 trunks, and the 48 port model support 16 trunks.

**Warranty and support**

- Limited Lifetime Warranty

See [hpe.com/officeconnect/support](https://www.hpe.com/officeconnect/support) for warranty and support information included with your product purchase.

## HPE OfficeConnect 1620 Switch Series



### Specifications

	<b>HPE OfficeConnect 1620 8 G Switch (JG912A)</b>	<b>HPE OfficeConnect 1620 24G Switch (JG913A)</b>	<b>HPE OfficeConnect 1620 48G Switch (JG914A)</b>
<b>I/O ports and slots</b>	8 RJ-45 autosensing 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only	24 RJ-45 autosensing 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only	48 RJ-45 autosensing 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only
<b>Additional ports and slots</b>	1 RJ-45 console port to access limited CLI port	1 RJ-45 console port to access limited CLI port	1 RJ-45 console port to access limited CLI port
<b>Physical characteristics</b>			
Dimensions	10.47(w) x 6.38(d) x 1.73(h) in (26.59 x 16.21 x 4.39 cm) (1U height)	17.32(w) x 6.81(d) x 1.73(h) in (43.99 x 17.3 x 4.39 cm) (1U height)	17.32(w) x 9.37(d) x 1.73(h) in (43.99 x 23.8 x 4.39 cm)
Weight	2.2 lb (1 kg)	4.85 lb (2.2 kg)	7.28 lb (3.3 kg)
<b>Memory and processor</b>	MIPS @ 500 MHz, 32 MB flash, 128 MB SDRAM; packet buffer size: 512 KB	MIPS @ 500 MHz, 32 MB flash, 128 MB SDRAM; packet buffer size: 4.1MB	MIPS @ 650 MHz, 32 MB flash, 128 MB SDRAM; packet buffer size: 512 KB 1.5 MB
<b>Mounting and enclosure</b>	Mounts in an EIA standard 19-inch telco rack or equipment cabinet (hardware included), wall mount	Mounts in an EIA standard 19-inch telco rack or equipment cabinet (hardware included)	Mounts in an EIA standard 19-inch telco rack or equipment cabinet (hardware included)
<b>Performance</b>			
100 Mb Latency	< 7 $\mu$ s	< 7 $\mu$ s	< 7 $\mu$ s
1000 Mb Latency	< 5 $\mu$ s	< 5 $\mu$ s	< 5 $\mu$ s
Throughput	up to 11.9 Mpps (64-byte packets)	up to 35.7 Mpps (64-byte packets)	up to 71.4 Mpps (64-byte packets)
Switching capacity	16 Gbps	48 Gbps	96 Gbps
MAC address table size	8192 entries	8192 entries	16384 entries
<b>Reliability</b>			
MTBF (years)	138.89	123.46	81.30

Specifications	HPE OfficeConnect 1620 8 G Switch (JG912A)	HPE OfficeConnect 1620 24G Switch (JG913A)	HPE OfficeConnect 1620 48G Switch (JG914A)
<b>Environment</b>			
Operating temperature	32°F to 104°F (0°C to 40°C)	32°F to 104°F (0°C to 40°C)	32°F to 104°F (0°C to 40°C)
Operating relative humidity	5% to 95%, noncondensing	5% to 95%, noncondensing	5% to 95%, noncondensing
Nonoperating/Storage temperature	-40°F to 158°F (-40°C to 70°C)	-40°F to 158°F (-40°C to 70°C)	-40°F to 158°F (-40°C to 70°C)
Nonoperating/Storage relative humidity	5% to 95%, noncondensing	5% to 95%, noncondensing	5% to 95%, noncondensing
Altitude	up to 16,404 ft (5 km)	up to 16,404 ft (5 km)	up to 16,404 ft (5 km)
Acoustic	No Fan	No Fan	Power: 49.7 dB, Pressure: 49.7 dB; ISO 7779
<b>Electrical characteristics</b>			
Frequency	50/60 Hz	50/60 Hz	50/60 Hz
AC voltage	100 - 240 VAC	100 - 240 VAC	100 - 240 VAC
Maximum power rating	7 W	15 W	28.2 W
	<b>Note:</b> Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.	<b>Note:</b> Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.	<b>Note:</b> Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.
<b>Safety</b>	IEC 60950-1; EN 60950-1; CSA 22.2 60950-1; UL 60950-1 2nd Edition	IEC 60950-1; EN 60950-1; CSA 22.2 60950-1; UL 60950-1 2nd Edition	IEC 60950-1; EN 60950-1; CSA 22.2 60950-1; UL 60950-1 2nd Edition
<b>Emissions</b>	FCC part 15 Class A; VCCI Class A; EN 55022 Class A; CISPR 22 Class A; EN 55024; EN 61000-3-2 2000, 61000-3-3; ICES-003 Class A	FCC part 15 Class A; VCCI Class A; EN 55022 Class A; CISPR 22 Class A; EN 55024; EN 61000-3-2 2000, 61000-3-3; ICES-003 Class A	FCC part 15 Class A; VCCI Class A; EN 55022 Class A; CISPR 22 Class A; EN 55024; EN 61000-3-2 2000, 61000-3-3; ICES-003 Class A
<b>Services</b>	Refer to the Hewlett Packard Enterprise website at <a href="http://hpe.com/networking/services">hpe.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.	Refer to the Hewlett Packard Enterprise website at <a href="http://hpe.com/networking/services">hpe.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.	Refer to the Hewlett Packard Enterprise website at <a href="http://hpe.com/networking/services">hpe.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.

**Standards and protocols**

(applies to all products in series)

---

**General protocols**

IEEE 802.1D MAC Bridges  
IEEE 802.1p Priority  
IEEE 802.1Q VLANs

IEEE 802.3 Type 10BASE-T  
IEEE 802.3ab 1000BASE-T  
IEEE 802.3ad Link Aggregation Control  
Protocol (LACP)

IEEE 802.3az Energy Efficient Ethernet  
IEEE 802.3i 10BASE-T  
IEEE 802.3x Flow Control

---

Learn more at  
[\*\*hpe.com/networking\*\*](http://hpe.com/networking)



Make the right purchase decision. Click here to chat with our presales specialists.



Sign up for updates

