

PRODUCT LINE MATRIX

ACCESS POINTS

CATEGORY	INDOOR							REMOTE	OUTDOOR				
FEATURE	AP-93H	AP-103	AP-104/105	AP-204/205	AP-114/115	AP-134/135	AP-224/225	RAP-3WN/RAP-3WNP	RAP-108/109	RAP-155/155P	AP-175P/AP-175AC	AP-274/AP-275	
													
NUMBER OF RADIOS	1	2	2	2	2	2	2	1	2	2	2	2	
SUPPORTED BANDS	Dual	Dual concurrent	Dual concurrent	Dual concurrent	Dual concurrent	Dual concurrent	Dual concurrent	2.4GHz	Dual concurrent	Dual concurrent	Dual concurrent	Dual concurrent	
WI-FI STANDARDS	802.11a/b/g/n	802.11a/b/g/n	802.11a/b/g/n	802.11a/b/g/n/ac	802.11a/b/g/n	802.11a/b/g/n	802.11a/b/g/n/ac	802.11b/g/n	802.11a/b/g/n	802.11a/b/g/n	802.11a/b/g/n	802.11a/b/g/n/ac	
RADIO MIMO TYPE	2x2:2	2x2:2	2x2:2	2x2:2	3x3:3	3x3:3	3x3:3	2x2:2	2x2:2	2x2:2 (2.4 GHz), 3x3:3 (5 GHz)	2x2:2	3x3:3	
MAX NUMBER OF BSSIDS (PER RADIO)	16	16	8	16	16	16	16	16	16	16	8	16	
MAX NUMBER OF ASSOCIATED CLIENTS PER RADIO	Tunnel: 255 Other: 110	Tunnel: 255 Other: 110	Tunnel: 255 Other: 110	255	Tunnel: 255 Other: 110	Tunnel: 255 Other: 110	255	Tunnel: 255 Other: 110	Tunnel: 255 Other: 110	Tunnel: 255 Other: 110	Tunnel: 255 Other: 110	255	
MAX TRANSMIT POWER (PER RADIO CHAIN, MCS0) 2.4 GHZ/5 GHZ	18 dBm 18 dBm	18 dBm 18 dBm	20 dBm 20 dBm	18 dBm 18 dBm	20 dBm 19 dBm	17 dBm 17 dBm	18 dBm 18 dBm	17 dBm	18 dBm 18 dBm	18 dBm 18 dBm	22 dBm 22 dBm	23 dBm 23 dBm	
RF CONNECTORS (RP-SMA)	No	No	4x (AP-104)	2x DB (AP-204)	3x DB (AP-114)	3x DB (AP-134)	3x DB (AP-224)	No	2x DB (RAP-108)	No	4 Nf	6 Nf (AP-274)	
INTEGRATED ANTENNAS	2x DB omni	2x omni downtilt	4x omni downtilt (AP-105)	4x omni downtilt (AP-205)	6x omni downtilt (AP-115)	omni downtilt (AP-135)	omni downtilt (AP-225)	2x 2.4 GHz omni	4x omni (RAP-109)	5x omni	N/A	3x 2.4 GHz omni (AP-275) 3x 5 GHz omni (AP-275)	
TPM MODULE	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
NETWORK INTERFACES	1x GE + 4x FE	1x GE	1x GE	1x GE	1x GE	2x GE	2x GE	3x FE	1x GE + 1x FE	5x GE	1x GE	2x GE	

CATEGORY	INDOOR							REMOTE	OUTDOOR				
FEATURE	AP-93H	AP-103	AP-104/105	AP-204/205	AP-114/115	AP-134/135	AP-224/225	RAP-3WN/RAP-3WNP	RAP-108/109	RAP-155/155P	AP-175P/AP-175AC	AP-274/AP-275	
													
LIFETIME WARRANTY	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	No	✓	
MINIMUM SOFTWARE VERSION	ArubaOS 6.1.3.0	ArubaOS 6.4.0.0 InstantOS 4.1.0.0	ArubaOS 3.4.1.0 (AP-105) ArubaOS 6.1.3.0 (AP-104) InstantOS 2.0.0.3	ArubaOS 6.4.1.0 InstantOS 4.2.0.0	ArubaOS 6.3.1.0 InstantOS 4.0.0.0	ArubaOS 6.1.1.0 InstantOS 2.0.0.3	ArubaOS 6.3.0.0 InstantOS 4.0.0.0	ArubaOS 6.1.4.0 InstantOS 3.0.0.0	ArubaOS 6.2.0.0 InstantOS 3.2.0.0	ArubaOS 6.3.0.0 InstantOS 3.3.0.1	ArubaOS 5.0.2.1 InstantOS 2.0.0.3	ArubaOS 6.4.0.0 InstantOS 4.1.0.0	
SPECTRUM ANALYSIS SUPPORT	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
MAXIMUM POWER CONSUMPTION (EXCLUDING USB, POE PSE)	8W (DC) 9W (PoE)	8W (DC) 9.5W (PoE)	10W (DC) 12.5W (PoE)	11.7W (DC) 12.5W (PoE)	12W (DC) 13W (PoE)	12W (DC) 13.5W (PoE)	15W (DC) 12.5W/15.5W (PoE)	4.0W/5.5W	12.5W	15.5W	18W	23W	
MAX IPSEC ENCRYPTED WIRED THROUGHPUT (RAP MODE)	10	10	15	20	20	40	20	20	20	100	15	20	



1344 CROSSMAN AVE | SUNNYVALE, CA 94089
 1.866.55.ARUBA | T: 1.408.227.4500 | FAX: 1.408.227.4550 | INFO@ARUBANETWORKS.COM